

Strilube 4160 is a Rust Preventive concentrate that provides an ease to the formulator in formulating Rust Preventives. It can be used in Oil based, Oil-solvent based and in solvent-based Rust Preventives. Strilube 4160 offers excellent dewatering and demulsibility even in presence of alkalinity.

### Physio-chemical properties

Tests	Test Method	Results
Appearance	Visual	Waxy Brown Semi-solid
Flash Point	ASTM D-92	>120°C
Melting Point	ASTM D-87	55°C
Acid Number	ASTM D-664	30 mgKOH/g
Calcium Content	Calculated	1.4%

**Application:** General Purpose Rust Preventives based on Oil or Solvent or Oil-Solvent system.

**Typical Treat Rate:** 2-12% by weight

**PACKING:** 180 Kg open mouth MS drums

**STORAGE CONDITIONS:** Store in a cool, dry place away from any direct source of heat and moisture. Maximum recommended storage temperature: 46°C (115°F)

**SOLUBILITY:** Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

**SHELF LIFE:** Best if used within 24 months from the date of manufacture.

**Manufactured by:**

STRIBECK ADDICHEM

Email: [lab@stribeckaddichem.com](mailto:lab@stribeckaddichem.com)

Web: [www.stribeckaddichem.com](http://www.stribeckaddichem.com)