

Strilube® 1021 is a gear oil additive package with excellent extreme pressure and demulsibility properties. It meets DIN 51517 part 3 (CLP) requirements of gear oil at 1.8% treat rate. The package is soluble in mineral oils as well as synthetic hydrocarbons.

### Physio-chemical properties

Tests	Test Method	Results
Appearance	Visual	Clear Yellow Liquid
Density at 29.5°C	ASTM D-1298	0.992 g/ml
Kinematic Viscosity at 40°C	ASTM D-445	24 Typical
Flash Point	ASTM D-92	>80°C
Nitrogen Content	ICP-AES	1.2%
Sulphur Content	ICP-AES	22.5%

**Application:** Industrial gear oil and slideway lubricants.

**PACKING:** 190 Kg (419 lbs) closed head drum

**STORAGE CONDITIONS:** Store in a cool, dry place away from any direct source of heat and moisture. Maximum recommended storage temperature: 46°C (115°F)

**SOLUBILITY:** Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

**SHELF LIFE:** Best if used within 24 months from the date of manufacture.

**Manufactured by:**  
STRIBECK ADDICHEM  
Email: lab@stribeckaddichem.com