

Strilube 1045 is an ashless R&O (Rust and Oxidation) additive package designed to protect lubricants. It features a blend of oxidation inhibitors and corrosion inhibitors for both ferrous and non-ferrous metals. Excellent solubility in mineral oils and synthetic base stocks. It exhibits outstanding antioxidant performance in ASTM D2272, RPVOT.

Physio-chemical properties

Tests	Test Method	Results
Appearance	Visual	Clear Yellow liquid
Density at 29.5°C	ASTM D-1298	0.960 g/ml
Kinematic Viscosity at 40°C	ASTM D-445	77 cSt (Typical)
Flash Point	ASTM D-92	>120°C
Nitrogen Content	ICP-AES	1.1%
Sulfur Content	ICP-AES	7.5%

TREAT RATE: 0.45% w/w.

PACKING: 190 Kg (419 lbs) closed head drum

STORAGE CONDITIONS: Store in a cool, dry place away from any direct source of heat and moisture. Maximum recommended storage temperature: 46°C (115°F)

SOLUBILITY: Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

SHELF LIFE: Best if used within 24 months from the date of manufacture.

Manufactured by:
STRIBECK ADDICHEM
Email: lab@stribeckaddichem.com