

Strilube® 1060 is an environmentally friendly hydraulic oil package refers to a formulation of hydraulic fluid that is designed to reduce environmental impact while still providing effective lubrication and hydraulic performance.

### Physio-chemical properties

Tests	Test Method	Results
Appearance	Visual	Yellow Clear liquid
Density at 29.5°C	ASTM D-1298	0.987 g/ml
Kinematic Viscosity at 40°C	ASTM D-445	180 cSt (Typical)
Nitrogen Content	-	5% Typical
Sulfur Content	ICP-AES	8% Typical

**Application:** Hydraulic Oils and industrial oil.

**Typical Treat Rate:** 1-1.5% by weight

**PACKING:** 200 Kg (419 lbs) closed head drum

**STORAGE CONDITIONS:** Store in a cool, dry place away from any direct source of heat and moisture. Maximum recommended storage temperature: 46°C (115°F)

**SOLUBILITY:** Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

**SHELF LIFE:** Best if used within 24 months from the date of manufacture.

**Manufactured by:**

STRIBECK ADDICHEM

Email: lab@stribeckaddichem.com