

Strilube® 1077 is a synergistic chemical blend of Sulfur and Phosphorus compounds. The package is soluble in mineral oils as well as synthetic hydrocarbons.

Strilube 1077 meets below requirements in Group I and II base oils:

GL-5 – 3.9% w/w

GL-4 – 2.0% w/w

CLP – 1.2% w/w

Physio-chemical properties

Tests	Test Method	Results
Appearance	Visual	Clear Yellow liquid
Density at 29.5°C	ASTM D-1298	1.02 g/ml
Kinematic Viscosity at 40°C	ASTM D-445	12 cSt (Typical)
Flash Point	ASTM D-92	>75°C
Phosphorus Content	ICP-AES	1.5%
Sulfur Content	ICP-AES	32%

PACKING: 190 Kg (419 lbs) closed head drum

STORAGE CONDITIONS: Store in a cool, dry place away from any direct source of heat and moisture. Maximum recommended storage temperature: 46°C (115°F)

SOLUBILITY: Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

SHELF LIFE: Best if used within 24 months from the date of manufacture.

Manufactured by:

STRIBECK ADDICHEM

Email: lab@stribeckaddichem.com