

Strilube®1081 is slideway and gear oil additive package. Gives Excellent Antiwear and Extreme Pressure performance. It also meets DIN 51517 part 3 (CLP) requirements of gear oil. Soluble in Group I and Group II base stocks. It compatible with other industrial oils and coolants.

Strilube 1081 meets below requirements at 1.75% in Group I and II base oils:

- GM LS-2
- Cincinnati Machine P-47, P-50, and P-53 way oil specifications

Physio-chemical properties

Tests	Test Method	Results
Appearance	Visual	Clear Pale Yellow
Density at 29.5°C	ASTM D-1298	0.97 g/ml
Kinematic Viscosity at 40°C	ASTM D-445	14 cSt (Typical)
Flash Point	ASTM D-92	>100°C
Phosphorous Content	ICP-AES	0.4%
Sulfur Content	ICP-AES	16%

Application: Strilube 1081 helps in minimizing friction, wear and stick-slip issue. It provides much-needed lubrication of slideways guide carriage and tailstock.

Typical Treat Rate: 1.75% by weight.

PACKING: 190 Kg (419 lbs) closed head drum.

STORAGE CONDITIONS: Store in a cool, dry place away from any direct source of heat and moisture. Maximum recommended storage temperature: 46°C (115°F)

SOLUBILITY: Soluble in petroleum and synthetic lubricant base stocks and most common solvents. Insoluble in water. However, it is recommended to verify the solubility in the base oils used and the compatibility with other additives.

SHELF LIFE: Best if used within 24 months from the date of manufacture.

Manufactured by:
STRIBECK ADDICHEM
Email: lab@stribeckaddichem.com